


Miniature PCB Power Relay

HG4115



FEATURES

- Most popular power relay
- Up to 30A switching capacity
- DC and AC coil available

TYPICAL APPLICATIONS

- Industrial controls
- Commercial applications
- Home appliances

CONTACT RATING

Form	Voltage	1 Form A (H)	1 Form B (D)	1 Form C (Z)	
				NO	NC
Resistive	240VAC 28VDC	30A 30A	15A 10A	20A 20A	10A 10A
Max. Switching Current		30A	15A	20A	10A
Max. Switching Voltage	277VAC/30VDC				
Max. Continuous Current		30A	15A	20A	10A
Max. Switching Power		8.31KVA, 900W	4.155KVA, 450W	5.54KVA, 600W	2.77KVA, 300W
Min. Load	1A, 5VDC/12VAC				

UL/CSA RATING

Load Type	Voltage	1 Form A (H)	1 Form B (D)	1 Form C (Z)	
				NO	NC
General Purpose	240VAC	30A	15A	20A	10A
Resistive	240VAC 28VDC	30A 20A	15A 10A	20A 20A	10A 10A
Motor	240VAC 120VAC	2HP 1HP	0.5HP 0.25HP	2HP 1HP	0.5HP 0.25HP
LRA/FLA	240VAC 120VAC	80A/30A 98A/22A	30A/10A	50A/20A	20A/7A
Tungsten	120VAC	TV5	TV3	TV5	TV3
Ballast	277VAC	10A	3A	10A	3A

CONTACT DATA

Material	AgCdO, AgSnOInO	
Initial Contact Resistance	50 mΩ, max. at 0.1A, 6VDC	
Service Life	Mechanical	10 ⁷ ops.
	Electrical	10 ⁵ ops.

COIL DATA

Type	Coil Voltage Code	Nominal Voltage (VDC/VAC)	Resistance (Ω)±10%	Power Consumption	Must Operate Voltage Max. (VDC/VAC)	Must Release Voltage Min. (VDC/VAC)
DC Coil	005	5	27	0.9W	3.75	0.5
	006	6	40		4.50	0.6
	009	9	97		6.75	0.9
	012	12	155		9.00	1.2
	024	24	660		18.00	2.4
	048	48	2,560		36.00	4.8
	110	110	10,330		82.50	11.0
AC Coil	012A	12	26	2VA	10.20	1.8
	024A	24	106		20.40	3.6
	110A	110	2,750		93.50	16.0
	120A	120	2,950		102.00	18.0
	220A	220	11,000		187.00	33.0
	240A	240	13,110		204.00	36.0

CHARACTERISTICS

Operate Time	15 ms for DC coil; 20 ms for AC coil, max.
Release Time	10 ms for DC coil; 15 ms for AC coil, max.
Insulation Resistance	1000 MΩ, at 500 VDC, 50%RH
Dielectric Strength	1500 Vrms, 1 min. between open contacts 1500 Vrms, 1 min. between coil and contacts
Shock Resistance	10 g, 11ms, functional; 100 g destructive
Vibration Resistance	DA 1.5mm, 10 - 55 Hz
Power Consumption	DC Coil: 0.9W; AC Coil: 2VA, approx.
Ambient Temperature	-55 to 85°C operating; -55 to 130°C storage
Weight	Open: 20g; Covered: 26g, approx.

ORDERING DESIGNATION

Example:	HG4115 /	012-	Z	1	C	F	6
Model							
Coil Voltage Code							
DC/AC							
Nil: DC Coil							
A: AC Coil							
Contact Form							
H: 1 Form A; D: 1 Form B; Z: 1 Form C							
Version							
Nil: Open; 1: Sealed; 2: Dust Cover							
Contact Material							
C: AgCdO; S: AgSnOInO							
Thermal Class							
Nil: UL Class B; F: UL Class F							
Creepage Distance							
Nil: UL 508 Spacing							
6: UL 873 Spacing							

OVERALL DIMENSIONS, MOUNTING HOLES AND WIRING DIAGRAMS (mm)

Overall Dimensions	
Mounting Holes (Bottom View)	Wiring Diagrams (Bottom View)

NOTES

1. All parameters, unless otherwise specified, are measured at ambient temperature 23°C.
2. In mounting holes drawing, the * holes is not needed for 1 Form A, the ** hole is not needed for 1 Form B. The *** hole is not needed for UL873 spacing version.
3. In wiring diagrams drawing the * terminal is not present for UL873 spacing version.
4. To exert optimum electrical life, please remove the tape of sealed version after cleaning process.
5. Custom-made services available with operational quantity. Please let us know your special requirements.
6. Specifications subject to change without prior notice.

T Y H Enterprise Limited
Room 1620B, Nan Fung Centre
264-298 Castle Peak Road
Tsuen Wan, N.T.
Hong Kong
Tel: 852-2416-0132
Fax: 852-2413-6229
http://www.tyhhk.com
email: info@tyhhk.com

Plant: Shanghai Hi-Gradex Relay Mfg. Co., Ltd
918 Shixin Road
Airport Town
Pudong New Area
Shanghai 201202
China
Tel: 86-21-6299-5619 / -5877
Fax: 86-21-6299-5619
email: tyhesh@online.sh.cn